



EX-TR 335-02Z-3G/D

- Metal enclosure
- Ex-Zone 2 and 22
- 40,5 mm x 76 mm x 38 mm
- 1 Cable entry M 20 x 1.5
- Mounting details to EN 50041
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

EX-TR 335-02Z-3G/D

103002249

EAN (European Article Number)

4030661423388

Explosion protection

BG-GS-ET-15

EN 60079-0

EN 60079-15

EN 60079-31

EN 60947-5-1

22

2

3D

3G

⊕ II 3G Ex nC IIC T5 Gc X

⊕ II 3D Ex tc IIIC T90°C Dc X

Manufacturer declaration

ATEX Zone 2 and 22

General data

Product name

EX-T 335 roller plunger _R

Housing construction form

Norm construction design

C

Enclosure material

Aluminium

Enclosure coating material

painted

Material of the contacts, electrical	Silver
Gross weight	238 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	0
Number of safety contacts	2

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Roller plunger
Mechanical life, minimum	30,000,000 Operations
Impact energy, maximum	4 J
Actuating force, minimum	17 N
Actuating speed, maximum	0.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	7 mm
Cable cross-section of the cable glands, maximum	12 mm
	0.75 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	116.6 mm
Length of sensor	38 mm
Width of sensor	40.5 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Opener (NC)
Switching principle	Slow action
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Ordering code

Product type description:

EX-(1)(2) 335-(3)Z(4)-(5)-(6)-(7)-3G/D

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

7H-2138 Roller lever 7H for position switches with safety function

1K Offset roller lever 1K

3K Angle roller lever 3K

(3)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

03 3 NC contact


UE Slow action with overlapping contacts

1297 Enclosure with transverse slotted holes


2138 Roller lever 7H for position switches with safety function

1637 Gold-plated contacts

Dimension/Product/Basic




| 46,3 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi




| 48,3 kB | .jpg | 352.778 x 117.475 mm - 1000 x 333
Pixel - 72 dpi

| 1,7 kB | .png | 74.083 x 24.694 mm - 210 x 70 Pixel - 72 dpi



| 48,8 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355
Pixel - 72 dpi

| 1,4 kB | .png | 74.083 x 26.458 mm - 210 x 75 Pixel - 72 dpi



| 6,6 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi

| 66,1 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi

| 51,1 kB | .cdr |

Illustration/Product/Function



ID: 235rz01

| 149,7 kB | .jpg | 352.778 x 799.394 mm - 1000 x 2266 Pixel - 72 dpi

| 15,2 kB | .cdr |

| 2,9 kB | .png | 74.083 x 167.922 mm - 210 x 476 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 222021-01-31T17:26:22+01:000501Europe/BerlinSun, 31 Jan 2021 17:26:22

+010022pmSunday.31pm31Europe/BerlinCET2601Europe/BerlinJanuary2021Sun, 31 Jan 2021 17:26:22

+010001pm31