



BNS 260-11/01Z-ST-R

- Long life
- Small body
- no mechanical wear
- 26 mm x 36 mm x 13 mm
- Insensitive to soiling
- Thermoplastic enclosure
- Concealed mounting possible
- Insensitive to transverse misalignment
- Connector 8 mm, 6-pole, Latching interlocking

Data

Ordering data

BNS 260-11/01Z-ST-R

101184364

EAN (European Article Number) 4030661321615

eCl@ss number, Version 9.0 27-27-24-02

Approval - Standards

TÜV

cULus

EAC

General data

BNS 260

IEC 60947-5-3

BG-GS-ET-14

Installation conditions
(mechanical)

quasi-flush

Enclosure material

Glass-fibre, reinforced thermoplastic

Gross weight

17.5 g

General data - Features

Coding

Yes

Number of openers

2

Number of shutters

1

Number of safety contacts

2

Safety appraisal

ISO 13849-1

Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d- Value Normally-closed
contact/Normally open contact 25,000,000 Operations
(NC/NO)

Mechanical data

Actuating element Magnet

Door hinge Right

Ensured switch distance "ON" S 5 mm

ao

Ensured switch distance "OFF" S 15 mm

ar

Notice (Switch distance Sn) Axial misalignment, a horizontal and vertical misalignment of the safety sensor and the actuator are tolerated. The possible misalignment depends on the distance of the active surfaces of the sensor and the actuator. The sensor remains active within the tolerance range.

Direction of motion Head-on to the active surface

Mechanical data - Connection technique

Terminal Connector Connector 8 mm, 6-pole, Latching interlocking

Mechanical data - Dimensions

Height of sensor 36 mm

Length of sensor 13 mm

Width of sensor 26 mm

Ambient conditions

IP67

Ambient temperature, minimum -25 °C

Ambient temperature, maximum +70 °C

Storage and transport
temperature, minimum -25 °C

Storage and transport
temperature, maximum +70 °C

Resistance to vibrations to EN
60068-2-6 10 ... 55 Hz, amplitude 1 mm

30 g / 11 ms

Electrical data

Voltage type	DC (direct current)
Switching voltage, maximum	30 VDC
Switching current, maximum	0.4 A
Switching capacity, maximum	10 VA
Switching frequency, maximum	5 Hz

Scope of delivery

Included in delivery	Actuators must be ordered separately.
----------------------	---------------------------------------

Accessory

BPS 260
SRB-E-301ST
SRB-E-201LC

Notes

Note (General)	The number in brackets indicate the PIN number of the connector.
----------------	--

Ordering code

Product type description:

BNS 260-(1)(2)Z(3)-(4)-(5)

(1)

11 1 NO contacts/1 NC contact

02 2 NC contact

(2)

without with diagnostic output

/01 1 NC contact

(3)

without without LED switching conditions display

G with LED switching conditions display

(4)

without Pre-wired cable

ST with connector

(5)

- L** Door hinge on left-hand side
- R** Door hinge on right-hand side

Pictures

Photo/Product/Catalogue




ID: kbns2f04

| 540,4 kB | .jpg | 352.778 x 287.161 mm - 1000 x 814 Pixel - 72 dpi

| 42,3 kB | .png | 74.083 x 60.325 mm - 210 x 171 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1bns2g03

| 2,9 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel - 72 dpi

| 24,9 kB | .cdr |

| 61,2 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695 Pixel - 72 dpi


Graphic/Product/Contact



ID: kbns2k26

| 79,8 kB | .jpg | 352.778 x 99.483 mm - 1000 x 282 Pixel - 72 dpi

Diagramm/Product/Curve




ID: kbns2d03

| 200,1 kB | .jpg | 352.778 x 233.892 mm - 1000 x 663 Pixel - 72 dpi

| 18,5 kB | .png | 74.083 x 49.036 mm - 210 x 139 Pixel - 72 dpi

| 36,8 kB | .cdr |

Diagramm/Product/Curve	Diagramm	Product	Curve
1		Constant Product	Linear Curve
2		Constant Product	Linear Curve
3		Constant Product	Linear Curve
4		Constant Product	Linear Curve
5		Constant Product	Linear Curve
6		Constant Product	Linear Curve
7		Constant Product	Linear Curve
8		Constant Product	Linear Curve
9		Constant Product	Linear Curve
10		Constant Product	Linear Curve
11		Constant Product	Linear Curve
12		Constant Product	Linear Curve
13		Constant Product	Linear Curve
14		Constant Product	Linear Curve
15		Constant Product	Linear Curve



ID: kbns2d02

| 200,9 kB | .jpg | 352.778 x 235.303 mm - 1000 x 667


Pixel - 72 dpi

| 19,2 kB | .png | 74.083 x 49.389 mm - 210 x 140

Pixel - 72 dpi

| 36,3 kB | .cdr |

Graphic/Clipart




ID: kbns2c01

| 1,7 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel

- 72 dpi

| 20,1 kB | .cdr |

Graphic/Product/PIN



ID: km8--k6b

| 17,4 kB | .cdr |

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 452021-01-31T06:43:45+01:00601Europe/BerlinSun, 31 Jan 2021 06:43:45

+010045amSunday.31am31Europe/BerlinCET4301Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:43:45

+010001am31