

## BNS 303-12Z 10,0M



- Ø M30
- Long life
- no mechanical wear
- Insensitive to soiling
- Thermoplastic enclosure
- Insensitive to transverse misalignment
- Suitable for food processing industry only in combination with BPS 303 SS

### Data

#### Ordering data

|                               |                   |
|-------------------------------|-------------------|
|                               | BNS 303-12Z 10.0M |
|                               | 101126911         |
| EAN (European Article Number) | 4030661049021     |
| eCl@ss number, Version 9.0    | 27-27-24-02       |

#### Approval - Standards

TÜV  
cULus  
EAC

#### General data

|                                      |                                       |
|--------------------------------------|---------------------------------------|
|                                      | BNS 303                               |
|                                      | IEC 60947-5-3                         |
|                                      | BG-GS-ET-14                           |
| Installation conditions (mechanical) | quasi-flush                           |
| Enclosure material                   | Glass-fibre, reinforced thermoplastic |
| Material of the nuts                 | Thermoplastic                         |
| Gross weight                         | 375 g                                 |

#### General data - Features

|                       |     |
|-----------------------|-----|
| Coding                | Yes |
| Number of openers     | 2   |
| Number of shutters    | 1   |
| Number of cable wires | 4   |

## Safety appraisal

ISO 13849-1

Mission Time

20 Year(s)

## Safety appraisal - Safety outputs

B10d- Value Normally-closed contact/Normally open contact (NC/NO)

25,000,000 Operations

## Mechanical data

Actuating element

Magnet

Ensured switch distance "ON"  $S_{ao}$

5 mm

Ensured switch distance "OFF"  $S_{ar}$

15 mm

Direction of motion

Head-on to the active surface

Tightening torque of nuts, maximum

3 Nm

## Mechanical data - Connection technique

Terminal Connector

Cable

Length of cable

10 m

Wire cross-section

0.3 mm<sup>2</sup>

Wire cross-section

23 AWG

PVC

## Mechanical data - Dimensions

M30

width across flats

36 BK

Length of sensor

44 mm

## Ambient conditions

IP67

Ambient temperature, minimum

-25 °C

Ambient temperature, maximum

+70 °C

Storage and transport temperature, minimum

-25 °C

Storage and transport temperature, maximum

+70 °C

Resistance to vibrations to EN 60068-2-6

10 ... 55 Hz, amplitude 1 mm

30 g / 11 ms

## Electrical data

Voltage type

AC (alternating current)

DC (direct current)

Switching voltage, maximum

100 VAC

Switching voltage, maximum

100 VDC

|                              |       |
|------------------------------|-------|
| Switching current, maximum   | 0.4 A |
| Switching capacity, maximum  | 10 W  |
| Switching frequency, maximum | 5 Hz  |

### Electrical data - Digital Output

|          |                              |
|----------|------------------------------|
| Versions | Miscellaneous, Reed contacts |
|----------|------------------------------|

### Scope of delivery

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Included in delivery                | Actuators must be ordered separately. |
| Delivery scope of Mounting material | 2x Mounting material M30 x 1.5 nuts   |

### Accessory

BPS 300  
 BPS 303  
 BPS 303 SS  
 SRB-E-301ST  
 SRB-E-201LC

### Notes

|                |                                                                                                                                                 |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Note (General) | Contact symbols shown for the closed condition of the guard device.<br>The contact configuration for versions with or without LED is identical. |
|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------|

### Ordering code

Product type description:

BNS 303-(1)Z(2)-(3)-(4)

(1)

**11** 1 NO contacts/1 NC contact

**12** 1 NO contact/2 NC contacts

**02** - / 2 NC contacts

**03** - / 3 NC contacts

(2)

**without** without LED switching conditions display

**G** with LED switching conditions display

(3)

**without** with cable

**ST** with connector M12

(4)

**2187** Individual contact outlet

**2211** higher switching distance

## Pictures

### Photo/Product/Catalogue




ID: kbns3f03

| 170,5 kB | .jpg | 352.778 x 118.533 mm - 1000 x 336  
Pixel - 72 dpi

| 11,3 kB | .png | 74.083 x 24.694 mm - 210 x 70 Pixel  
- 72 dpi

### Dimension/Product/Basic



ID: 1bns3g02

| 30,4 kB | .cdr |

| 5,7 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel  
- 72 dpi

| 66,5 kB | .jpg | 352.778 x 245.886 mm - 1000 x 697  
Pixel - 72 dpi


### Graphic/Product/Contact



ID: k2o1sk05

| 43,5 kB | .jpg | 352.778 x 61.736 mm - 1000 x 175  
Pixel - 72 dpi

### Diagramm/Product/Curve



ID: kbns3a02

| 148,1 kB | .jpg | 352.778 x 201.436 mm - 1000 x 571  
Pixel - 72 dpi

| 118,4 kB | .cdr |

| 17,7 kB | .png | 74.083 x 42.333 mm - 210 x 120  
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 562021-01-31T06:53:56+01:000601Europe/BerlinSun, 31 Jan 2021 06:53:56

+010056amSunday.31am31Europe/BerlinCET5301Europe/BerlinJanuary2021Sun, 31 Jan 2021 06:53:56

+010001am31