



TQ 700-02

- Position indicator
- Thermoplastic enclosure
- Large wiring compartment
- 1 Cable entry M 20 x 1.5
- Twisting of towing eye not possible
- one-side operation / wire up to 10 m long
- One tension force for cable lengths up to 10 m

Data

Ordering data

	TQ 700-02
	101192480
EAN (European Article Number)	4030661352701
eCl@ss number, Version 9.0	27-27-06-07

Approval - Standards

TÜV
EAC

General data

	TQ 700
	IEC/EN 60947-5-1
Enclosure material	Glass-fibre, thermoplastic
Material of the contacts, electrical	Silver
Material of the cover	Glass-fibre, thermoplastic
Length of the wire, maximum	10 m
Gross weight	230 g

General data - Features

Number of openers	2
-------------------	---

Safety appraisal

ISO 13849-1

Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 100,000 Operations

B10d Normally open contact (NO) 100,000 Operations

Mechanical data

Mechanical life, minimum 1,000,000 Operations

Mechanical data - Connection technique

Terminal Connector Screw connection

0.75 mm²

2.5 mm²

Note (Cable section) All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Width 40.5 mm

Height 160 mm

Depth 42.2 mm

Ambient conditions

Protection class IP 67 to IEC/EN 60529

Ambient temperature, minimum -25 °C

Ambient temperature, maximum +70 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage 6 kV

Electrical data

Thermal test current 10 A

Utilisation category AC-15 230 VAC

Utilisation category AC-15 4 A

Utilisation category DC-13 24 VDC

Utilisation category DC-13	4 A
Switching element	Opener (NC)
Switching principle	Creep circuit element

Notes

Note (General)	Recommended cable lengths for pull-wire Emergency-Stop switches in relation to the range of ambient temperature. As the thimbles are subject to deformation in case of wire pull, the wire should be pulled several times after fitting. After that, the wire must be re-tensioned using the eyebolt or the tensioner. At 2 m ... 5 m distance intermediate wire supports are required, see accessories
----------------	--

Ordering code

Product type description:

TQ 700-(1)

(1)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts

Pictures


Photo/Product/Catalogue



ID: ktq70f01

| 38,6 kB | .png | 74.083 x 111.125 mm - 210 x 315
Pixel - 72 dpi
| 493,4 kB | .jpg | 352.778 x 529.167 mm - 1000 x
1500 Pixel - 72 dpi

Dimension/Product/Basic



ID: 1tq-7g01

| 10,3 kB | .png | 74.083 x 51.506 mm - 210 x 146


Pixel - 72 dpi

| 113,3 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695

Pixel - 72 dpi

| 181,4 kB | .cdr |

Graphic/Product/Contact




ID: ktf--k10

| 59,7 kB | .jpg | 352.778 x 195.439 mm - 1000 x 554

Pixel - 72 dpi

| 16,1 kB | .cdr |

Diagramm/Product/Curve



ID: kzq70d02

| 90,7 kB | .jpg | 352.778 x 352.778 mm - 1000 x 1000

Pixel - 72 dpi

| 3,0 kB | .png | 74.083 x 74.083 mm - 210 x 210 Pixel
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 522021-01-31T16:39:52+01:000401Europe/BerlinSun, 31 Jan 2021 16:39:52

+010052pmSunday.31pm31Europe/BerlinCET3901Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:39:52

+010001pm31