

EX-ZV14H 235-02Z-3D



- Metal enclosure
- 30 mm x 63,5 mm x 30 mm
- 1 Cable entry M 20 x 1.5
- Mounting details to EN 50047
- Wide range of alternative actuators
- Lever angle adjustable in 10° steps
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°
- Snap action with constant contact pressure up to switching point

Data

Ordering data

	EX-ZV14H 235-02Z-3D
	101193992
EAN (European Article Number)	4030661357904
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

IMMETRO

Explosion protection

EN 60079-15
EN 60079-31
IEC 60079-0
22
2
3D
3G
⊕ II 3G Ex nC IIC T5 Gc X
⊕ II 3D Ex tc IIIC T90°C Dc X

Manufacturer declaration ATEX Zone 2 and 22

General data

Product name	EX-Z 235 roller lever 14H EN 60947-5-1 BG-GS-ET-15
Housing construction form	Norm construction design
Enclosure material	Zink
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Lever material	Metal film
Roller material	Plastic
Gross weight	250 g

General data - Features

Safety functions	Yes
Number of safety contacts	2

Safety appraisal

	ISO 13849-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	20,000,000 Operations
Actuating speed, minimum	687 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Actuating torque, minimum	0.2 Nm
Positive break torque	0.2 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection
Cable cross-section of the cable glands, minimum	6 mm
Cable cross-section of the cable glands, maximum	12 mm
	0.75 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Wire cross-section	13 AWG
--------------------	--------

Mechanical data - Dimensions

Height of sensor	114 mm
Length of sensor	46 mm
Width of sensor	30 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	1 A
Switching element	Opener (NC)
Switching principle	Snap switch element
Bounce duration, maximum	3 ms
Switching frequency	5,000 /h
Switchover time, maximum	5.5 ms

Ordering code

Product type description:

EX-(1)(2) 235-(3)Z-(4)-(5)-(6)-(7)-
3D

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

4S Plunger 4S

4R Roller plunger 4R

1R Offset roller lever 1R
K Offset roller lever K
3K Angle roller lever 3K
4K Angle roller lever 4K
K4 Angle roller lever K4
1H Roller lever 1H
7H Roller lever 7H
10H Rod lever 10H
12H Roller lever 12H
14H Roller lever 14H

(3)

02 2 NC contact

11 1 NO contacts/1 NC contact

20 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

(4)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(5)

1297 Enclosure with transverse slotted holes

(6)

2138 Roller lever 7H for position switches with safety function

(7)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k235hf05


| 331,6 kB | .jpg | 107.244 x 324.203 mm - 304 x 919

Pixel - 72 dpi

| 216,2 kB | .png | 74.083 x 223.661 mm - 210 x 634

Pixel - 72 dpi


Dimension/Product/Basic



ID: k-235g01

| 111,2 kB | .jpg | 352.778 x 293.511 mm - 1000 x 832 Pixel - 72 dpi
 | 24,5 kB | .cdr |
 | 3,6 kB | .png | 74.083 x 61.736 mm - 210 x 175 Pixel - 72 dpi


Dimension/Product/Basic



ID: 1xzm1g07

| 2,5 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel - 72 dpi
 | 46,3 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691 Pixel - 72 dpi


Diagramm/Product/Travel



ID: kh235s05

| 27,5 kB | .cdr |
 | 104,1 kB | .jpg | 352.778 x 193.322 mm - 1000 x 548 Pixel - 72 dpi
 | 3,1 kB | .png | 74.083 x 40.569 mm - 210 x 115 Pixel - 72 dpi


Graphic/Product/Contact



ID: k2o--k01

| 48,8 kB | .jpg | 352.778 x 125.236 mm - 1000 x 355 Pixel - 72 dpi
 | 1,4 kB | .png | 74.083 x 26.458 mm - 210 x 75 Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1h236g05

| 25,9 kB | .cdr |

| 82,4 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695

Pixel - 72 dpi

| 7,6 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 552021-01-31T17:21:55+01:000501Europe/BerlinSun, 31 Jan 2021 17:21:55

+010055pmSunday.31pm31Europe/BerlinCET2101Europe/BerlinJanuary2021Sun, 31 Jan 2021 17:21:55

+010001pm31