

XT7C40PC440H29

capacitive sensor - XT7 - 40 x 40 x 117 - plastic
- Sn 15 mm - 12..48 V DC



Main

Range of product	OsiSense XT
Sensor type	Capacitive proximity sensor
Product specific application	Detection of insulated materials
Sensor name	XT7
Sensor design	Form 40 x 40 x 117
Size	117 mm
Body type	Plug-in body
Detector flush mounting acceptance	Flush mountable
Material	Plastic
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	4-wire
[Sn] nominal sensing distance	15 mm
Discrete output function	1 NC + 1 NO
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Screw clamp terminal, 4 x 1.5 mm ²
[Us] rated supply voltage	12...48 V DC
Maximum delay response	5 ms
IP degree of protection	IP67 conforming to IEC 60529

Complementary

Detection face	5 positions turret head
Differential travel	< 0.2 x Sr
Repeat accuracy	< 0.1 x Sr
Cable entry	1 entry tapped for M20 x 1.5 cable gland, cable outer diameter: 7...13 mm
Status LED	Supply state indication: 1 LED (green) Output state indication: 1 LED (yellow)
Supply voltage limits	10...58 V DC
Protection type	Short-circuit protection
Switching frequency	<= 100 Hz
Maximum voltage drop	<2 V (closed)
Current consumption	<= 10 mA
Maximum delay first up	30 ms
Maximum delay recovery	5 ms
Maximum switching current	200 mA
Marking	CE
Setting-up	Sensitivity by potentiometer
Depth	40 mm
Height	117 mm
Width	40 mm
Net weight	0.22 kg

Environment

Product certifications	CSA UL
Ambient air temperature for operation	-25...70 °C

Packing Units

Package 1 Weight	0.001 kg
Package 1 Height	1.450 dm
Package 1 width	0.800 dm
Package 1 Length	0.440 dm

Contractual warranty


Warranty	18 months
----------	-----------

- (1) Output LED
- (2) Supply LED
- (3) 1 tapped entry for M20 x 1.5
- (4) 2 elongated holes $\varnothing 5.3 \times 7$

Setting-up

Minimum Mounting Distances (mm)


Side by side



$e(1)$ 40

$\geq$

Face to face



$e(2)$ 120

$\geq$

Wiring Diagram

3-wire DC NO + NC Output

