

XCMD2110AM4

limit switch XCMD - metal end plunger - 1NC
+1NO - snap - AMP 4P



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch
Device short name	XCMD
Sensor design	Miniature
Body type	Plug-in body
Head type	Plunger head
Material	Metal
Body material	Zamak
Head material	Zamak
Fixing mode	By the body
Movement of operating head	Linear
Type of operator	Spring return plunger metal
Type of approach	Lateral approach, 2 directions
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Snap action

Complementary

Switch actuation	By 30° cam
Electrical connection	Male connector AMP connector, 4 pins
Contacts insulation form	Zb
Positive opening	With
Positive opening minimum force	42.5 N
Minimum force for tripping	8.5 N
Maximum actuation speed	0.5 m/s
[Ie] rated operational current	1 A at 24 V, DC-13 conforming to EN/IEC 60947-5-1 appendix A 3 A at 24 V, AC-14
[Ithe] conventional enclosed thermal current	6 A
[Ui] rated insulation voltage	36 V (pollution degree 3) conforming to IEC 60947-5-1
Maximum resistance across terminals	25 mOhm conforming to IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	IEC 60664 0.8 kV IEC 60947-1 0.8 kV
Short-circuit protection	6 A cartridge fuse, type gG
Electrical durability	5000000 cycles, DC-13, 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Mechanical durability	10000000 cycles
Width	32 mm
Height	78 mm
Depth	16 mm
Net weight	0.09 kg






Environment

Shock resistance	25 gn for 18 ms conforming to IEC 60068-2-27
Vibration resistance	5 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
IP degree of protection	IP66 conforming to IEC 60529 IP69 conforming to IEC 60529
IK degree of protection	IK06 conforming to EN 62262
Electrical shock protection class	Class III conforming to IEC 61140 Class III conforming to NF C 20-030
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Protective treatment	TC
Product certifications	CURus CCC
Standards	UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60204-1

Packing Units

Package 1 Weight	0.085 kg
Package 1 Height	1.600 dm
Package 1 width	5.300 dm
Package 1 Length	6.100 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Technical drawing of the 1000 Series Ball Valve. The drawing includes a side view and a front view. Dimensions are provided in millimeters (mm) and inches (in.).

Side View Dimensions:

- Top flange outer diameter: $\varnothing 7$ in.
- Top flange inner diameter: $\varnothing 0.27$ in.
- Body length: 16 mm (0.62 in.)
- Bottom flange length: 17.6 mm (0.69 in.)

Front View Dimensions:

- Top flange outer diameter: $\varnothing 7$ in.
- Top flange inner diameter: $\varnothing 0.27$ in.
- Body length: 58.1 mm (2.28 in.)
- Bottom flange length: 17.6 mm (0.69 in.)
- Bottom flange outer diameter: 31.9 mm (1.25 in.)
- Bottom flange inner diameter: 20 mm (0.78 in.)
- Overall height: 78.1 mm (3.07 in.)

Angle Dimensions:


- Angle between the top flange and the body: 15°
- Angle between the bottom flange and the body: 15°



Connections and Schema


Wiring Diagram

2-pole NC + NO Snap Action



Connections and Schema

AMP Superseal 1.5 Male Connector




- 1 : NC
- 2 : NC
- 3 : NO
- 4 : NO

Technical Description



Characteristics of Actuation

Switch Actuation on End



Technical Description

Functional Diagram, Travel Distance



- (2)
- (3)
- (4)
- (5)

(P) : Positive opening point
 (1) : NC contact with positive opening operation
 (2) : Closed
 (3) : Open
 (4) : Tripping
 (5) : Resetting
 BK : Black
 WH : White
 BU : Blue
 BN : Brown