



T4VH336-11YR-1058

- Double-insulated
- Design to EN 50041
- suitable for elevators
- Thermoplastic enclosure
- 1 Cable entry M 20 x 1.5
- Wide range of alternative actuators
- Lever angle adjustable in 10° steps
- Also available with large rubber roller
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	T4VH 336-11YR-1058
	101142571
EAN (European Article Number)	4030661125671
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

cULus
CCC
EAC

General data

Product name	336 roller lever H-1058
Housing construction form	Norm construction design
	A
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Lever material	Metal film
Roller material	rubber
Gross weight	190 g

General data - Features

Suitable for elevators	Yes
------------------------	-----

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

	BG-GS-ET-15 ISO 13849-1 EN 60947-5-1
Mission Time	20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	20,000,000 Operations
-----------------------------------	-----------------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	30,000,000 Operations
Actuating speed, maximum	2.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note (Switchover time)	Switchover time in accordance with actuating speed
Actuating torque, minimum	0.3 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection 0.75 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor	144.5 mm
Length of sensor	38 mm
Width of sensor	40.5 mm

Ambient conditions

	IP67
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	10 A
Required rated short-circuit current to EN 60947-5-1	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	NO contact, NC contact
Switching principle	Creep circuit element
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Pictures


Photo/Product/Catalogue



ID: k336hf04

| 619,4 kB | .jpg | 237.419 x 504.119 mm - 673 x 1429
Pixel - 72 dpi
| 81,1 kB | .png | 74.083 x 156.986 mm - 210 x 445
Pixel - 72 dpi

Dimension/Product/Basic




ID: 1-336g01

| 51,4 kB | .cdr |
| 107,0 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695
Pixel - 72 dpi
| 4,1 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

Diagramm/Product/Travel

ID: kh335s05




| 2,4 kB | .png | 74.083 x 24.342 mm - 210 x 69 Pixel - 72 dpi

| 25,4 kB | .cdr |

| 66,9 kB | .jpg | 352.778 x 116.064 mm - 1000 x 329 Pixel - 72 dpi

Dimension/Product/Actuator




ID: 1h336g07

| 97,4 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi

| 25,7 kB | .cdr |

| 4,4 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi

Dimension/Product/Actuator



ID: kh336g07

| 106,6 kB | .jpg | 352.778 x 239.889 mm - 1000 x 680 Pixel - 72 dpi

| 23,7 kB | .cdr |

| 4,4 kB | .png | 74.083 x 50.447 mm - 210 x 143 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 402021-01-31T04:57:40+01:000401Europe/BerlinSun, 31 Jan 2021 04:57:40

+010040amSunday.31am31Europe/BerlinCET5701Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:57:40

+010001am31