



T1K 335-02Z

- Metal enclosure
- Design to EN 50041
- 40,5 mm x 76 mm x 38 mm
- 1 Cable entry M 20 x 1.5
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	T1K 335-02Z
	101165928
EAN (European Article Number)	4030661212890
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

cULus
CCC
EAC

General data

Product name	T 335 offset roller lever 1K
Housing construction form	Norm construction design
Enclosure material	Aluminium
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Gross weight	190 g

General data - Features

Safety functions	Yes
Number of safety contacts	2

Safety appraisal

BG-GS-ET-15
ISO 13849-1
EN 60947-5-1

Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 20,000,000 Operations

Mechanical data

Actuating element Offset roller lever
Mechanical life, minimum 30,000,000 Operations
Actuating force, minimum 17 N
Actuating speed, maximum 0.5 m/s
Note (Actuating speed) Actuating speed with actuating angle 30° to switch axis
Note (Switchover time) Switchover time in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector Screw connection
0.75 mm²
2.5 mm²
Note (Cable section) All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor 118.5 mm
Length of sensor 38 mm
Width of sensor 40.5 mm

Ambient conditions

IP67
Ambient temperature, minimum -30 °C
Ambient temperature, maximum +80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage 6 kV

Electrical data

Thermal test current 10 A
Required rated short-circuit current to EN 60947-5-1 1,000 A
Utilisation category AC-15 230 VAC
Utilisation category AC-15 4 A

Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	Opener (NC)
Switching principle	Slow action
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Ordering code

Product type description:

(1)(2) 3(3)5-(4)Z(5)-(6)-(7)-(8)-(9)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

3 slim design

5 large design

(4)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts (not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

12 1 NO contact/2 NC contacts

03 3 NC contact

(5)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(6)

G24 with LED

- (7)
- without** Cable entry M20
- NPT** Cable entry NPT 1/2"
- ST** M12 connector with A-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)
- ST-2310** M12 connector with B-coding (Caution! According to EN 60204-1, the versions with connector must only be used in PELV circuits.)

- (8)
- 2138** Roller lever 7H for position switches with safety function

- (9)
- 1637** Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k335kf01

| 124,4 kB | .png | 74.083 x 164.747 mm - 210 x 467
Pixel - 72 dpi
| 486,9 kB | .jpg | 159.103 x 354.542 mm - 451 x 1005
Pixel - 72 dpi

Photo/Product/Catalogue



ID: k335sf01

| 156,7 kB | .png | 74.083 x 166.511 mm - 210 x 472
Pixel - 72 dpi
| 454,9 kB | .jpg | 136.172 x 306.211 mm - 386 x 868
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 532021-01-31T04:30:53+01:00401Europe/BerlinSun, 31 Jan 2021 04:30:53

+010053amSunday.31am31Europe/BerlinCET3001Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:30:53

+010001am31