XZCC20FCM30B

female, 1/2 20UNF, 3-pin, elbowed connector - cable gland Pg 7



Main	
Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Elbowed female connector 1/2 20 UNF, 3 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <0.75 mm² / clamping capacity 36 mm

Complementary

Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
[Ue] rated operational voltage	250 V AC	
[In] rated current	4 A	
Enclosure material	Plastic	
Minimum insulating resistance	1000 GΩ	
Contact resistance	8000 μOhm	
Net weight	0.02 kg	
Net weight	0.02 kg	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-4085 °C

Packing Units

Package 1 Weight	0.024 kg	
Package 1 Height	0.200 dm	
Package 1 width	0.360 dm	
Package 1 Length	0.400 dm	

Offer Sustainability

REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
€Yes
-


Contractual warranty

Contractad warranty	
Warranty	18 months

Product data sheet Dimensions Drawings

XZCC20FCM30B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Product data sheet Connections and Schema

XZCC20FCM30B

Connections and Schemes

