



MD 461-22Y

- Metal enclosure
- 2 cable entries M 20 x 1.5
- Lever can be transposed by 180°
- 118 mm x 155 mm x 64 mm (basic component)
- Continuous adjustment of lever position 360°
- Actuator head can be repositioned in steps 4 x 90°
- In temperature-resistant version, the roller can be mounted in two different positions on the shaft

Data

Ordering data

	MD 461-22Y
	101059618
EAN (European Article Number)	4030661036885
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

DNV.GL
EAC

General data

Product name	461 roller lever D EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	2,285 g

General data - Features

Number of openers	2
Number of shutters	2

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)	2,000,000 Operations
-----------------------------------	----------------------

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	5,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	max. 2 x 2.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection
	1.5 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	293 mm
Length of sensor	64 mm
Width of sensor	118 mm
Width of Castor	9 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	4 kV
---------------------------------	------

Electrical data

Thermal test current	16 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Switching element	NO contact / NC contact
Switching principle	Snap switch element
Bounce duration, maximum	5 ms
Switchover time, maximum	35 ms

Pictures

Photo/Product/Catalogue



ID: bt441f09

| 63,1 kB | .png | 74.083 x 129.822 mm - 210 x 368

Pixel - 72 dpi

| 159,1 kB | .jpg | 147.108 x 257.881 mm - 417 x 731

Pixel - 72 dpi

Photo/Product/Catalogue



ID: kt461f01


| 76,0 kB | .png | 73.731 x 122.061 mm - 209 x 346

Pixel - 72 dpi

| 1,1 MB | .jpg | 352.778 x 582.436 mm - 1000 x 1651

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1t461g01

| 110,5 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691

Pixel - 72 dpi

| 9,2 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 35,2 kB | .cdr |

Diagramm/Product/Travel


ID: kt441s12



| 1,3 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel
- 72 dpi

| 78,0 kB | .jpg | 352.778 x 260.703 mm - 1000 x 739
Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t422b08

| 121,4 kB | .jpg | 352.778 x 243.769 mm - 1000 x 691
Pixel - 72 dpi

| 10,2 kB | .png | 74.083 x 51.153 mm - 210 x 145
Pixel - 72 dpi

Illustration/Product/Function



ID: 235hz05

| 15,2 kB | .cdr |

| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124
Pixel - 72 dpi

| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 552021-01-31T15:56:55+01:000301Europe/BerlinSun, 31 Jan 2021 15:56:55

+010055pmSunday.31pm31Europe/BerlinCET5601Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:56:55

+010001pm31