





**M30 CYLINDRICAL DIRECT DIFFUSE & RETRO-REFLECTIVE  
ULTRASONIC SENSOR WITH TEACH-IN BUTTON**

- M30 ultrasonic sensor with standard housing and with large front with high performances and high sensing distances
- Adjustable hysteresis function: models with double digital programmable output specific for level detection
- Models with voltage or current output: programmable slope to optimize resolution
- Adjustable working area (window mode or object mode) by Teach-in button on all models for a quick and easy installation
- Two multifunction LEDs: orange LED for adjustment procedure and output type and green LED for target alignment
- Plastic and AISI 316L stainless steel housing, plug M12 or cable exit 4 pin



**Detection properties**

|                          |                       |
|--------------------------|-----------------------|
| Nominal sensing distance | 3500mm                |
| Thermal drift of Sr      | ±5%                   |
| Repeat Accuracy          | 0,1%valore fondoscala |
| Beam angle               | 12° ± 2°              |
| Resolution               | 0,1%valore fondoscala |
| Sensitivity adjustment   | Teach-In cable        |
| Hysteresis               | 1% valore fondoscala  |

|                                       |                      |
|---------------------------------------|----------------------|
| thermal compensation                  | Si                   |
| Minimum sensing distance (blind zone) | 250mm                |
| Linearity error                       | 1% valore fondoscala |

## Application

|                    |                    |
|--------------------|--------------------|
| Function Principle | Diffuse reflection |
|--------------------|--------------------|

## Outputs

|                     |                      |
|---------------------|----------------------|
| Output type         | 2x PNP               |
| Output Function     | NO/NC multifunctions |
| Switching frequency | 1Hz                  |
| Response time       | 1s                   |

## Electrical data

|                                  |                             |
|----------------------------------|-----------------------------|
| Operating Voltage                | 10 - 30Vdc                  |
| No-Load supply current           | 25mA                        |
| Load current                     | 100mA                       |
| Leakage current                  | ≤ 10µA @ 30Vdc              |
| Output voltage drop              | 2,2V max @ IL=100mA         |
| Max ripple content               | 5%                          |
| LED indicators                   | Verde: Eco - Giallo: Uscita |
| Time delay before availability   | ≤400ms                      |
| Short-circuit protection         | Si                          |
| Reverse Polarity Protection      | Si                          |
| Impulsive Overvoltage Protection | Si                          |

## Mechanical data

|                       |                      |
|-----------------------|----------------------|
| Dimensions            | M30 x 1,5 / L = 98mm |
| Weight                | 140g                 |
| Housing Material      | PBT                  |
| Connections           | M12 Plug             |
| Tightening torque     | 1,5Nm                |
| Operating temperature | -20°C...+70°C        |
| Storage temperature   | -30°C...+80°C        |
| Transducer Frequency  | 112KHz               |
| Diameter/Dimension    | M30                  |

## Test/Approvals

|                       |                        |
|-----------------------|------------------------|
| Approvals             | CE cULus               |
| EMC compatibility     | IEC 60947-5-2          |
| Shocks and vibrations | IEC EN 60947-5-2 / 7.4 |

Degree of protection

IP67

### Accessories

Supplied Accessories

2 x M30x1,5 dadi, 2 rosette Ø 30

### Generical Data

Dimensions

M30 x 1,5 / L = 98mm

Operating Temperature

-20°C...+70°C

Mechanical Protection

IP67

---

### Datasensing S.r.l.

Strada S.Caterina, 235  
41122 Modena (MO)  
Tel. 059 420411  
Fax 059 253973  
E-mail [info@datasensing.com](mailto:info@datasensing.com)

### date of printing

29/04/2022 11:01:02