



TR336-11ZUE-M20

- slim design
- Double-insulated
- Design to EN 50041
- Thermoplastic enclosure
- 1 Cable entry M 20 x 1.5
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	TR 336-11ZUE
	101060427
EAN (European Article Number)	4030661042862
eCl@ss number, Version 9.0	27-27-26-01

Approval - Standards

cULus
CCC
EAC

General data

Product name	336 roller plunger _R
Housing construction form	Norm construction design C
Enclosure material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Material of the contacts, electrical	Silver
Gross weight	105 g

General data - Features

Safety functions	Yes
Number of auxiliary contacts	1
Number of safety contacts	1

Safety appraisal

BG-GS-ET-15
ISO 13849-1
EN 60947-5-1

Mission Time

20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC)

20,000,000 Operations

Mechanical data

Actuating element

Roller plunger

Mechanical life, minimum

30,000,000 Operations

Actuating force, minimum

17 N

Actuating speed, maximum

0.5 m/s

Note (Actuating speed)

Actuating speed with actuating angle 30° to switch axis

Note (Switchover time)

Switchover time in accordance with actuating speed

Mechanical data - Connection technique

Terminal Connector

Screw connection

0.75 mm²

2.5 mm²

Note (Cable section)

All indications about the cable section are including the conductor ferrules.

Mechanical data - Dimensions

Height of sensor

116.5 mm

Length of sensor

38 mm

Width of sensor

40.5 mm

Ambient conditions

IP67

Ambient temperature, minimum

-30 °C

Ambient temperature, maximum

+80 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage

6 kV

Electrical data

Thermal test current

10 A

Required rated short-circuit current to EN 60947-5-1

1,000 A

Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	NO contact, NC contact
Switching principle	Slow action with overlapping contacts
Bounce duration, maximum	2 ms
Switching frequency	5,000 /h

Ordering code

Product type description:

(1)(2) 336-(3)Z(4)-(5)-(6)-(7)

(1)

Z Snap action

T Slow action (not available for AF/S)

(2)

S Plunger S

R Roller plunger R

H Roller lever H

10H Rod lever 10H

7H Roller lever 7H

1K Offset roller lever 1K

3K Angle roller lever 3K

RMS Brass roller

(3)

11 1 NO contacts/1 NC contact

02 2 NC contact

20 2 NO contacts, (switches with 2 NO contacts are not suitable for safety applications)

01/01 1 NC contact left / 1 NC contact right

(4)

H Slow action with staggered contacts

UE Slow action with overlapping contacts

(5)

without Cable entry M20

NPT Cable entry NPT 1/2"

ST M12 connector with A-coding

ST-2310 M12 connector with B-coding

(6)

2138 Roller lever 7H for position switches with safety function

(7)

1637 Gold-plated contacts

Pictures

Photo/Product/Catalogue



ID: k336rf01


| 325,8 kB | .jpg | 135.819 x 316.442 mm - 385 x 897

Pixel - 72 dpi

| 158,7 kB | .png | 74.083 x 172.508 mm - 210 x 489

Pixel - 72 dpi

Dimension/Product/Basic



ID: 1-336g01


| 51,4 kB | .cdr |

| 107,0 kB | .jpg | 352.778 x 245.181 mm - 1000 x 695

Pixel - 72 dpi

| 4,1 kB | .png | 74.083 x 51.506 mm - 210 x 146 Pixel
- 72 dpi

Diagramm/Product/Travel



ID: kr335s09


| 43,1 kB | .jpg | 352.778 x 112.536 mm - 1000 x 319

Pixel - 72 dpi

| 20,4 kB | .cdr |

| 1,8 kB | .png | 74.083 x 23.636 mm - 210 x 67 Pixel
- 72 dpi

Graphic/Product/Contact




ID: k1o1sk01

| 52,2 kB | .jpg | 352.778 x 143.581 mm - 1000 x 407

Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1r336g01

| 6,6 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi

| 66,1 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi

| 51,1 kB | .cdr |

Illustration/Product/Function



ID: 235rz01

| 149,7 kB | .jpg | 352.778 x 799.394 mm - 1000 x
2266 Pixel - 72 dpi

| 15,2 kB | .cdr |

| 2,9 kB | .png | 74.083 x 167.922 mm - 210 x 476
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 272021-01-31T04:47:27+01:000401Europe/BerlinSun, 31 Jan 2021 04:47:27

+010027amSunday.31am31Europe/BerlinCET4701Europe/BerlinJanuary2021Sun, 31 Jan 2021 04:47:27

+010001am31