



TJ 064-03Y

- Metal enclosure
- 3 or 4 Contacts
- 2 cable entries M 25 x 1.5
- 184 mm x 111 mm x 149 mm (basic component)
- Actuator heads can be repositioned by 4 x 90°

Data

Ordering data

	TJ 064-03Y
	101057481
EAN (European Article Number)	4030661027036
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

cULus
 CCC
 EAC

General data

Product name	064 offset roller lever J
	EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Grey cast iron, galvanised
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	3,495 g

General data - Features

Number of openers	3
-------------------	---

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Actuating element	Offset roller lever
Mechanical life, minimum	1,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	45 °
Contact opening	2 x 4 mm
Actuating speed, minimum	600 mm/min
Actuating speed, maximum	1 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 4 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	11 AWG

Mechanical data - Dimensions

Height of sensor	90 mm
Length of sensor	149 mm
Width of Castor	9 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage	6 kV
---------------------------------	------

Electrical data

Thermal test current	25 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	25 A

Switching element	Opener (NC)
Note (Switching element)	with double break
Switching principle	Creep circuit element
Switching frequency	1,000 /h

Notes

Note (General)	Actuation from the right should be avoided, since this reduces the mechanical life of the position switch.
----------------	--

Ordering code

Product type description:

T(1) 064-(2)Y-(3)

(1)

S Plunger S

J Offset roller lever J

X Offset roller lever X

(2)

03 3 NC contact

12 1 NO contact/2 NC contacts

21 2 NO contacts/1 NC contact

30 3 NO contacts

04 4 NC contact

13 1 NO contacts/3 NC contact

22 2 NO contacts/2 NC contact

31 3 NO contacts/1 NC contact

40 4 NO contacts

(3)

UE Slow action with overlapping contacts

H Slow action with staggered contacts

R Latching 2 x 45°

Pictures

Photo/Product/Catalogue

Illustration/Product/Function



ID: 235rz03



| 131,9 kB | .jpg | 352.778 x 773.642 mm - 1000 x 2193 Pixel - 72 dpi

| 15,5 kB | .cdr |

| 2,7 kB | .png | 74.083 x 162.278 mm - 210 x 460 Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 352021-01-31T16:10:35+01:000401Europe/BerlinSun, 31 Jan 2021 16:10:35

+010035pmSunday.31pm31Europe/BerlinCET1001Europe/BerlinJanuary2021Sun, 31 Jan 2021 16:10:35

+010001pm31