




Indicative image

7 X 30 X 50 MM CUBIC CAPACITIVE SENSORS

- DC supply voltage
- No adjustable sensitivity
- Flat polycarbonate plastic housing



Detection properties

Nominal sensing distance	5mm
Thermal drift of Sr	< 20%
Repeat Accuracy	5%
Sensitivity adjustment	NO
Hysteresis	≤ 20%

Outputs

Output type	NPN
Output Function	NO
Switching frequency	10Hz

Electrical data

Operating Voltage	5Vdc
No-Load supply current	≤ 10mA
Load current	≤ 50mA
Leakage current	≤ 100μA

Output voltage drop	1,5Vmax @ IL=50mA
Max ripple content	≤10%
Time delay before availability	≤100ms
Short-circuit protection	Yes, autoreset
Reverse Polarity Protection	Yes
Impulsive Overvoltage Protection	Yes

Mechanical data

Mounting	Shielded
Dimensions	50x30x7mm
Weight	70g
Housing Material	noryl
Connections	2m PVC cable
Active Head Material	noryl
Operating temperature	0...60°C (without freeze)
Storage temperature	-30°C...+75°C
Diameter/Dimension	50x30x7mm


Test/Approvals

Approvals	CE
EMC compatibility	IEC 60947-5-2
Degree of protection	IP67

Generical Data

Dimensions	50x30x7mm
Operating Temperature	0...60°C (without freeze)
Mechanical Protection	IP67

ELECTRICAL DIAGRAMS OF THE CONNECTIONS



Datasensing S.r.l.

Strada S.Caterina, 235
41122 Modena (MO)
Tel. 059 420411
Fax 059 253973
E-mail info@datasensing.com

date of printing

13/04/2022 12:07:06