





Inductive sensor

NMB6-F104M-E2-C-FE-200MM-V3

- Sensing range 6 mm
- Ferrous targets
- Stainless steel sensing face
- Weld field immune
- Weld slag resistant coating
- 200 mm M8 male cordset with burn-proof POC jacket
- Power and output LEDs



Dimensions



Technical Data

General specifications

Switching function		Normally open (NO)
Output type		PNP
Rated operating distance	s_n	6 mm
Installation		flush
Assured operating distance	s_a	0 ... 4.86 mm
Actuating element		Ferrous targets
Reduction factor r_{Al}		0
Reduction factor r_{Cu}		0
Reduction factor r_{304}		0.6 ... 0.8
Reduction factor r_{Si37}		1
Output type		3-wire

Nominal ratings

Operating voltage	U_B	10 ... 30 V DC
Switching frequency	f	2 Hz
Hysteresis	H	5 ... 15 typ. 10 %

Release date: 2020-03-24 Date of issue: 2020-03-30 Filename: 915201_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com


Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Technical Data

Reverse polarity protection		reverse polarity protected
Short-circuit protection		yes
Voltage drop	U_d	$\leq 2\text{ V}$
Operating current	I_L	$\leq 100\text{ mA}$
Current consumption		$\leq 22\text{ mA}$
Off-state current	I_r	$\leq 10\text{ }\mu\text{A}$
Indicators/operating means		
Operation indicator		Dual LED Green: power Yellow: output
Standard conformity		
Standards		EN 60947-5-2:2007 IEC 60947-5-2:2007
Approvals and certificates		
CCC approval		CCC approval / marking not required for products rated $\leq 36\text{ V}$
Ambient conditions		
Ambient temperature		$-25 \dots 70\text{ }^\circ\text{C}$ ($-13 \dots 158\text{ }^\circ\text{F}$)
Mechanical specifications		
Connection type		Cable connector M8 x 1 , 3-pin with orange POC cable 200 mm
Core cross-section		0.34 mm^2
Housing material		Xylan coated , Stainless steel 1.4305 / AISI 303
Degree of protection		IP67

Connection



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
3	BU	(blue)
4	BK	(black)