



UV10H 432Y

- 2 Contacts
- Metal enclosure
- Epoxy resin rod
- 3 cable entries M 20 x 1.5
- Lever can be transposed by 180°
- 62 mm x 80 mm x 50 mm (basic component)
- Continuous adjustment of lever position 360°
- Switching points and contact function adjustable
- Actuator head can be repositioned in steps 4 x 90°

Data

Ordering data

	UV10H 432Y
	101060554
EAN (European Article Number)	4030661046778
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

EAC

General data

Product name	U 432 rod lever 10H EN 60947-5-1
Active principle	mechanical
Enclosure material	Light alloy die-casting
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Material of the rod	Epoxy resin
Gross weight	545 g

General data - Features

Number of openers	2
-------------------	---

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 2,000,000 Operations

Mechanical data

Actuating element	Rod lever
Mechanical life, minimum	10,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.5 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis

Mechanical data - Connection technique

Terminal Connector	Screw connection 1.5 mm ² 2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	280 mm
Length of sensor	50 mm
Width of sensor	62 mm
Diameter of the Rod	6 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-20 °C
Ambient temperature, maximum	+60 °C

Electrical data

Thermal test current	16 A
Switching element	Opener (NC)
Switching principle	Creep circuit element

Notes

Note (General) Type of contact and switching points can be factory set to order.

Ordering code

Product type description:

U(1) 432Y-(2)-(3)

(1)

S Plunger S

K Offset roller lever K

8H Roller lever 8H

H Roller lever H

3H Roller lever 3H

7H Roller lever 7H

4H Spring rod lever on shaft 4H

9H Rod lever 9H

10H Rod lever 10H

2H Leaf spring lever 2H

6H Leaf spring lever 6H

(2)

without 2 NC contact

2S 2 NO contacts

1S/10E 1 NO contacts/1 NC contact

(3)

1272 Version for low temperatures to -30 °C

Pictures

Photo/Product/Catalogue




ID: ku43hf10

| 99,9 kB | .png | 74.083 x 203.2 mm - 210 x 576 Pixel
- 72 dpi

| 416,4 kB | .jpg | 164.747 x 452.614 mm - 467 x 1283
Pixel - 72 dpi

Dimension/Product/Basic

ID: 1u43-g02



| 82,9 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701 Pixel - 72 dpi
| 3,7 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel - 72 dpi
| 27,7 kB | .cdr |


Diagramm/Product/Travel

ID: ku43-s03



| 93,9 kB | .jpg | 352.778 x 182.386 mm - 1000 x 517 Pixel - 72 dpi
| 1,2 kB | .png | 74.083 x 52.564 mm - 210 x 149 Pixel - 72 dpi


Graphic/Product/Contact



ID: k2o1sk02

| 18,4 kB | .cdr |
| 82,3 kB | .jpg | 352.778 x 193.322 mm - 1000 x 548 Pixel - 72 dpi


Illustration/Product/Function



ID: ku432a01

| 19,8 kB | .png | 74.083 x 49.742 mm - 210 x 141 Pixel - 72 dpi
| 203,1 kB | .cdr |
| 157,4 kB | .jpg | 352.778 x 236.361 mm - 1000 x 670 Pixel - 72 dpi


Illustration/Product/Function



ID: 235hz03

| 140,4 kB | .jpg | 352.778 x 733.072 mm - 1000 x 2078 Pixel - 72 dpi
| 2,5 kB | .png | 74.083 x 153.811 mm - 210 x 436 Pixel - 72 dpi
| 15,5 kB | .cdr |

Dimension/Product/Actuator



ID: 1t15vb10

| 4,5 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi

| 95,6 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 242021-01-31T15:33:24+01:00301Europe/BerlinSun, 31 Jan 2021 15:33:24

+010024pmSunday.31pm31Europe/BerlinCET3301Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:33:24

+010001pm31