



MV3H 017-22Y

- 4 Contacts
- Metal enclosure
- 3 Cable entry M 20 x 1.5
- Lever can be transposed by 180°
- 67 mm x 130 mm x 43 mm (basic component)
- Continuous adjustment of lever position 360°
- Actuator head can be repositioned in steps 4 x 90°

Data

Ordering data

	MV3H 017-22Y
	101060371
EAN (European Article Number)	4030661041056
eCl@ss number, Version 9.0	27-27-06-01

Approval - Standards

CCC
EAC

General data

Product name	017 roller lever 3H EN 60947-5-1
Active principle	mechanical
Slide form	Castor
Enclosure material	Light-alloy diecast, paint finish
Enclosure coating material	painted
Material of the contacts, electrical	Silver
Roller material	Plastic
Gross weight	525 g

General data - Features

Number of openers	2
-------------------	---

Number of shutters	2
--------------------	---

Mechanical data

Actuating element	Roller lever
Mechanical life, minimum	5,000,000 Operations
Actuating angle, from left of switch axis	30 °
Actuating angle, from right of switch axis	30 °
Contact opening	2 x 1.2 mm
Actuating speed, minimum	1 mm/min
Actuating speed, maximum	3 m/s
Note (Actuating speed)	Actuating speed with vertical actuating angle to switch axis
Actuating torque	0.2 Nm

Mechanical data - Connection technique

Terminal Connector	Screw connection
	1.5 mm ²
	2.5 mm ²
Note (Cable section)	All indications about the cable section are including the conductor ferrules.
Wire cross-section	13 AWG

Mechanical data - Dimensions

Height of sensor	226 mm
Length of sensor	43 mm
Width of sensor	67 mm
Width of Castor	8 mm
Diameter of Castor	36 mm

Ambient conditions

Protection class	IP 65 to IEC/EN 60529
Ambient temperature, minimum	-30 °C
Ambient temperature, maximum	+90 °C

Electrical data

Thermal test current	10 A
Utilisation category AC-15	400 VAC
Utilisation category AC-15	2.5 A
Switching element	NO contact, NC contact
Note (Switching element)	galvanically separated contact bridges
Switching principle	Snap switch element
Bounce duration, maximum	2.5 ms
Switchover time, maximum	40 ms

Ordering code

Product type description:

(1)(2) 017-(3)Y-(4)

(1)

T Slow action (not available for AF/S)

M Snap action

(2)

S Plunger S

2S Telescopic plunger 2S

K Offset roller lever K

2K Tilt lever 2K

3K Angle roller lever 3K

8H Roller lever 8H

7H Roller lever 7H

10H Rod lever 10H

H Roller lever H

4H Spring rod lever on shaft 4H

2H Leaf spring lever 2H

3H Roller lever 3H

9H Rod lever 9H

6H Leaf spring lever 6H

(3)

22 2 NO contacts/2 NC contact

13 1 NO contacts/3 NC contact

31 3 NO contacts/1 NC contact

(4)

UE Slow action with overlapping contacts

H Slow action with staggered contacts

C Magnetic blow-out

Pictures

Photo/Product/Catalogue




ID: kts17f07

| 87,4 kB | .png | 74.083 x 180.975 mm - 210 x 513
Pixel - 72 dpi

| 1.007,9 kB | .jpg | 352.778 x 863.247 mm - 1000 x
2447 Pixel - 72 dpi

Dimension/Product/Basic




ID: 1t017g01

| 30,5 kB | .cdr |

| 9,1 kB | .png | 74.083 x 51.153 mm - 210 x 145 Pixel
- 72 dpi

| 187,6 kB | .jpg | 352.778 x 365.831 mm - 1000 x
1037 Pixel - 72 dpi

Graphic/Product/Contact




ID: k2o2sk04

| 19,1 kB | .cdr |

| 81,1 kB | .jpg | 352.778 x 379.236 mm - 1000 x 1075
Pixel - 72 dpi

Dimension/Product/Actuator



ID: 1t15vb04

| 9,3 kB | .png | 74.083 x 52.211 mm - 210 x 148 Pixel
- 72 dpi

| 93,3 kB | .jpg | 352.778 x 248.003 mm - 1000 x 703
Pixel - 72 dpi

Illustration/Product/Function



ID: 235hz05



| 15,2 kB | .cdr |

| 180,5 kB | .jpg | 352.778 x 749.3 mm - 1000 x 2124

Pixel - 72 dpi

| 3,4 kB | .png | 74.083 x 157.339 mm - 210 x 446

Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 042021-01-31T15:28:04+01:000301Europe/BerlinSun, 31 Jan 2021 15:28:04

+010004pmSunday.31pm31Europe/BerlinCET2801Europe/BerlinJanuary2021Sun, 31 Jan 2021 15:28:04

+010001pm31