



T3Z 068-22YRG

- Robust design
- Metal enclosure
- Low actuating force
- 2 switches in one enclosure
- two-side operation / wire up to 2 x 50 m long

Data

Ordering data

	T3Z 068-22yrG
	101087883
EAN (European Article Number)	4030661057231
eCl@ss number, Version 9.0	27-37-12-01

Approval - Standards

cCSAus
CCC
EAC

General data

	T3Z 068
	IEC 60947-5-1
	IEC 60947-5-5
	ISO 13850
Enclosure material	Grey cast iron, painted
Material of the contacts, electrical	Silver
Material of the cover	Grey cast iron, painted
Length of the wire, maximum	50 m
Gross weight	4,835 g

General data - Features

Indicator lamp	Yes
Reset by pull ring	Yes
Number of auxiliary contacts	2

Number of safety contacts 2

Safety appraisal

ISO 13849-1
Mission Time 20 Year(s)

Safety appraisal - Safety outputs

B10d Normally-closed contact (NC) 100,000 Operations

Mechanical data

Actuating element Roller lever N300
Mechanical life, minimum 50,000 Operations
Positive break angle 32 °
Actuating force, maximum 50 N
Note (Actuating force) 30 N in wire direction
Actuation direction Each time 75° right-hand side and left-hand side rotation
Positive break force, minimum 50 N
Positive break torque 0.2 Nm

Mechanical data - Connection technique

Terminal Connector Screw connection
0.75 mm²
1.5 mm²
Note (Cable section) All indications about the cable section are including the conductor ferrules.

Ambient conditions

Protection class IP 65 to IEC/EN 60529
Ambient temperature, minimum -30 °C
Ambient temperature, maximum +90 °C

Ambient conditions - Insulation value

Rated impulse withstand voltage 4 kV

Electrical data

Thermal test current 10 A
Utilisation category AC-15 230 VAC
Utilisation category AC-15 2.5 A
Utilisation category DC-13 24 VDC
Utilisation category DC-13 6 A
Electrical power consumption 5 W
Switching element NO contact, NC contact

Switching principle

Creep circuit element

Status indication

Colour of the indicator lamp

Yellow

Notes

Note (General)

At 3 m distance intermediate wire supports are required, see accessories

Ordering code

Product type description:

T3Z 068-(1)YR(2)(3)

(1)

11 1 NO contacts/1 NC contact

22 2 NO contacts/2 NC contact

33 3 NO contacts / 3 NC contacts (not combinable in combination with -2909)

(2)

without Reset by pull ring

S Key reset (not combinable in combination with -2909)

(3)

without without indicator lamp

G with indicator lamp (not combinable in combination with -2909)

2909 Outside parts in stainless steel

Pictures

Photo/Product/Catalogue




ID: kt3z0f02

| 786,3 kB | .jpg | 352.778 x 480.131 mm - 1000 x 1361 Pixel - 72 dpi

| 56,3 kB | .png | 73.731 x 100.542 mm - 209 x 285 Pixel - 72 dpi


Dimension/Product/Basic



ID: 1t3z0g01

| 118,6 kB | .jpg | 352.778 x 247.297 mm - 1000 x 701
Pixel - 72 dpi
| 9,9 kB | .png | 74.083 x 51.858 mm - 210 x 147 Pixel
- 72 dpi
| 43,4 kB | .cdr |


Diagramm/Product/Travel



ID: kt3z0s03

| 89,4 kB | .jpg | 352.778 x 171.097 mm - 1000 x 485
Pixel - 72 dpi
| 2,6 kB | .png | 74.083 x 35.983 mm - 210 x 102 Pixel
- 72 dpi

Dimension/Other



ID: kt3z0g02

| 3,3 kB | .png | 74.083 x 43.744 mm - 210 x 124 Pixel
- 72 dpi
| 31,2 kB | .cdr |
| 93,5 kB | .jpg | 352.778 x 208.844 mm - 1000 x 592
Pixel - 72 dpi

K.A. Schmersal GmbH & Co. KG, Möddinghofe 3, D-42279 Wuppertal

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on 182021-01-31T07:15:18+01:000701Europe/BerlinSun, 31 Jan 2021 07:15:18

+010018amSunday.31am31Europe/BerlinCET1501Europe/BerlinJanuary2021Sun, 31 Jan 2021 07:15:18

+010001am31